



ODC SL75

ODC SL75, A BESPOKE WINDOW SYSTEM, WITH A SLIMLINE VENT AND FRAME WHICH PERFORMS TO ENHANCED THERMAL INSULATION AND SECURITY STANDARDS.

With the energy efficiency of buildings under increasing scrutiny, specifying the right window systems is critical in modern building design. The ODC SL75 window system's U value from 0.9 and uses a unique polyamide thermal barrier for superior thermal performance, and the system also attains the highest level of weather performance for water tightness, air permeability and wind resistance.

This unique and expertly engineered window suite offers the discerning homeowner the perfect combination of exceptionally slim frames and the highest of levels of performance. With sleek, clean lines, these beautifully designed windows can transform the appearance of any home, adding value to the property whilst also making it warmer, brighter and more secure.

ODC Door & Glass Systems Ltd.

EMAIL: sales@odcglass.co.uk www.odcglass.co.uk

CLARITY IN DESIGN



ODC SL75



THERMAL PERFORMANCE

- Industry-leading thermal insulation
- Double- and triple-glazed options
- Unique thermal insulation profiles
- U-value of 1.3 W/m²K with standard DGU (Double Glazed Unit)*
- U-value of 0.9 W/m²K with standard TGU (Triple Glazed Unit)
- Window energy rating of A++
- BFRC registered and accredited

CASEMENT SIZES

TOP HUNG

- Max. vent size 1200mm (W) x 1340mm (H)
- Min. vent size 424mm (W) x 250mm (H)

SIDE HUNG

- Max. vent size 740mm (W) x 1300mm (H)
- Min. vent size. 250mm (W) x 424mm (H)
- Fixed lights 5m²
- Glazing thickness to 34mm
- Vent weight to 40kg

PEACE AND QUIET

Not only is the frame of the ODC SL75 window designed to help eliminate unwanted noise, the system is also flexible enough to allow a glazed unit up to 34mm thick to be specified. This makes it possible to incorporate some quite sophisticated acoustic glazing, which makes a huge difference if you live near a busy road, a railway or an airport.

TRIED AND TESTED

The ODC SL75 window is purpose-built and has been put through the most stringent test regime, ensuring that it is one of the highest performing and most reliable windows available.

- Premium-quality materials
- Highest levels of performance
- Industry-leading weather resistance

Opening Lights:

- Air permeability Class 4 600Pa
- Water-tightness Class 9A 600Pa
- Wind resistance Class C4/1600Pa**

Fixed Lights:

- Air permeability Class 4 600Pa
- Water-tightness Class 9A 600Pa
- Wind resistance Class A5 2000Pa**

SAFE AND SECURE

- One of the most secure windows available
- Optional enhanced security with hinge-side security brackets
- Multi-point locking mechanism
- Lockable handle

* With 1.0 W/m² DGU and high performance warm edge spacer.

** Exposure category varies with Width/Height of window and mullion/transom used, as these are the only unsupported members.



FOR MORE EXAMPLES OF OUR WORK VISIT WWW.ODCGLASS.CO.UK OR VISIT OUR SHOWROOMS:

LONDON: 97 Bollo Lane, London W3 8BN

POOLE: Sterte Road Industrial Estate, 145 Sterte Road, Poole, Dorset BH15 2AF

SALES: 03300 586 792 CUSTOMER SERVICES: 03300 586 793

CLARITY IN DESIGN



SLIDING DOORS



FOLDING DOORS



WINDOWS



ROOFS & ROOFLIGHTS



GLASS STRUCTURES



DOORS